

# DataPage II LITE



*The Scope™ DataPage II Lite is a compact desktop numeric encoder/transmitter on-site paging terminal. The unit has a 9,999 pager capacity. The system operates on 12 Volts DC supplied by a 115VAC-wall adapter. The unit comes with a four-inch helical antenna, BNC terminated.*



---

## FEATURES

- ◆ Accommodates 9,999 numeric pages
- ◆ Range up to 1 mile
- ◆ Ease of Operation
- ◆ Select 512 or 1200 Baud Transmission
- ◆ Industry Standard POCSAG Transmission



# Data Page II

## LITE

### SPECIFICATION SHEET

<b>Operating / Input Voltage</b>	<b>12 Volts DC, Wall AC Adapter UL Approved</b>
<b>Operating Current</b>	<b>100mA standby, 300mA Transmit</b>
<b>Frequency</b>	<b>457.575 Mhz</b>
<b>Adjacent Channel</b>	<b>&lt;200nW @4.5Khz deviation at 25Khz channel spacing @ 512 or 1200 Baud</b>
<b>Deviation</b>	<b>± 4.5 Khz</b>
<b>Stability</b>	<b>± 2.5ppm @ 14° to 132°F</b>
<b>Paging Format</b>	<b>POCSAG</b>
<b>RF Baud Rate</b>	<b>512, 1200</b>
<b>Type Accepted</b>	<b>FCC Part 90</b>
<b>FCC ID</b>	<b>JRNUSASERILINK</b>
<b>Size</b>	<b>7.75"W x 1.75"H x 7.5"D</b>
<b>Weight</b>	<b>1.6 Lbs without AC Adapter</b>
<b>Antenna</b>	<b>Electrical ¼ Wave, 4" Helical 90° BNC Terminated</b>